I AND

ECOS Environmentally Friendly Mobile Wash and Reclaim System

LANDA

- 4.7 GPM at 3500 PSI
- Carries up to 400 gallons
- Captures, filters, and recycles wash water for continuous use
- Honda Engine and belt-drive LT Pump with 7-year warranty



- Vacuum / Water Reclaim System with 50 feet of 2-inch vacuum hose and draggable, non-tipping suction head provides continuous suction of wash water.
- Multi-Stage Filtering System includes a 40 gallon holding tank with a 500 micron mesh/ 200 micron mesh Pre-Filter Intake Bag, a 50 micron Pleated Polyester Filter (20 micron on LX and DX models), a 20 micron Pleated Polyester Filter (5 micron on LX and DX models), and an Oil Absorbent Media Bag. Clean water is directed to selected tanks for reuse, or can be dumped directly to drain, pending local EPA requirements.
- Honda GX660 Engine and belt-drive LT Pump with 7-year warranty provide 4.7 GPM at 3500 PSI of cleaning might.
- Durable Swing-Away Tongue (rated for 7.500 lbs) connects with either a 2 5/16-inch Ball Coupler or Lunette Ring (DX model), 7-pin Electrical Trailer Plug and heavy-duty 2,000 Ib. capacity Swivel Jack, allowing trailer to be stored in a smaller area.

- Efficient Duracoil with stainless steel top wrap and 5-year warranty heats water using high-efficiency 120-Volt Burner.
- Heavy-Duty 4,000 Watt Generator produces reliable 120V AC power to the burner and vacuum.
- Two Hose Reels hold up to 100 ft. of highpressure hose and 75 ft. of low-pressure hose.
- 30 in. x 7 ft. Galley allows for storage of pressure washer equipment with a removable rear gate.
- Locked compartment includes Dual Fuel Tanks for gasoline engine (17 gallons) and diesel burner (17 gallons). Also includes space for two detergent buckets.
- Conveniently placed Locked Control Panel includes key start, choke, Burner On/Off Switch, Adjustable Thermostat, and an Hour Meter with low oil indicator. Also includes reclaim pump, vacuum motor switches and Low Point Drain for water tanks.

- Four Polvethvlene Water Tanks provide 400 gallons of clean water and are linked for even distribution. Main Control Valve System includes easy to use valves for controlling water distribution. Feed Pump with pressure-sensing switch alleviates wear and tear on main pump.
- Four 15-inch Black-Rim Wheels with 205/75/ R15D tires on Tandem Axles rated at 3,500 lbs each (7,000 lbs total) with Electric Brakes on both axles and battery operated Breakaway Kit for added safety.
- . Four Color-Coded Quick-Couple Nozzles made of hardened stainless steel are mounted near hose reel for ready access.
- Safety Features including redundant devices such as a Rupture Disk, and high-temperature shutdown to guard against excessive pressure or heat.



ECOS

FOR A BETTER TOMORROW...CLEAN GREEN!

Our revolutionary, patented ECOS Mobile Wash and Reclaim System* recovers, filters and recycles the dirty water from pressure washing for safe disposal or reuse—meeting most municipal and environmental regulations.



Galley storage compartment underneath the floor allows for easy storage of the vacuum hose. Shown with garden hose (not included).

Model #	Version	Part #	GPM	PSI	Pump RPM	Engine	CCs	GVWR (lbs)	Water Tank	Ship Wt (lbs)
EC0S-7000	Standard	1.103-825.0	4.7	3500	1360	Honda GX690	688	6,000	400 gal	3500
EC0S-7000	LX	1.103-838.0	4.7	3500	1360	Honda GX690	688	6,000	400 gal	3500
EC0S-7000	DX	1.103-839.0	4.7	3500	1360	Honda GX690	688	6,000	400 gal	3500

Dimensions: 174"L x 75"W x 74"H

Field Installed Options & Accessories

8.739-074.0	Tuff-Skin 6000 PSI Hose, 100'
8.922-019.0	Spare Tire Kit, ECOS Trailer - No Panel (tire not included)
8.922-020.0	Spare Tire Kit, ECOS Trailer - With Panel (tire not included)
8.752-044.0	Tire/Wheel Assembly, Black, 15" Radial
8.903-606.0	Water Jet Surface Cleaner
Replacemen	t Filters and Parts
8.726-045.0	5 Micron Carbon Filter Cartridge
8.726-044.0	20 Micron Pleated Filter Cartridge
8.754-082.0	200 Micron Pre-Filter Nylon Sock
8.726-046.0	Oil Absorbent Sock
8.919-317.0	Vacuum Nozzle Head Assembly with Guard
Drain Covers	and Water Dikes
8.751-135.0	Drain Cover, 36" x 36", 30oz PVC
8.751-136.0	Drain Cover, 48" x 48", 30oz PVC
8.751-137.0	Drain Cover, 48" x 48", Urethane
8.751-138.0	Water Dike, 10', 22oz PVC
8.751-139.0	Water Dike, 10', 40oz Urethane
8.751-140.0	Water Dike, 20', 22oz PVC
8.751-141.0	Water Dike, 20', 40oz Urethane

DETERGENT FOR EVERY JOB

Landa innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.



Specifications

Pressure Washer System	Trailer				
Engine Fuel: Gasoline (17-gallon tank)	Water Tank Capacity: 400 gallons				
Pump: LT (1360 RPM)	Gross Vehicle: 6,000 lbs.				
Generator: 4,000 watts/120VAC	Weight Rating (GVWR)				
Wand: Variable pressure with 50' hose	Trailer Axles: Dual, 3,500 lbs. each				
Detergent: Downstream detergent injector	both with electric brakes				
Multi-Stage Filter System	Wheels: 15-inch wheels, ST205/75/R15D tires				
Pre-Filter: 500 micron mesh	Swing-Away Tongue: 7,500 lb. capacity,				
200 micron mesh intake bag	25/16-inch ball coupler (standard/LX series)				
Oil Removal: Oil absorbent media bag	or adjustable lunette hitch (DX series)				
Sediment: 50 micron pleated polyester	Swivel Jack: 2,000 lb. capacity				
(20 micron on LX/DX Series)	Safety Chains: Dual 5/16-inch steel link				
Polish: 20 micron pleated polyester	with latching hooks				
(5 micron on LX/DX Series)	Lights: DOT approved recessed lights,				
Heating System	license plate holder				
Coil: 1/2" Schedule 80	LED lights (LX/DX Series only)				
Burner Fuel: Diesel/kerosene/fuel oil	Reflective conspicuity tape (LX/DX Series only)				
(17-gallon tank)	Dimensions: 174"L x 75"W x 73.5"H				
BTUs: 440,000	(with swing-away tongue extended)				
Vacuum System	Dry Weight: 2,865 lbs.				
Suction: 105 CFM	Shipping Dimensions: 161"L x 85"W x 82"H				
Hose: 50' x 2" diameter	(pallet & crate)				

Your Authorized Landa Dealer: